

LISTING OF THE CLAIMS

Claims 1-62. (Cancelled)

63. (Currently Amended) A method of continuously redirecting data messages between a messaging host system and a wireless mobile communication device, comprising:

~~receiving a data message at the messaging host system for a user, wherein the data message is received from a sender and addressed to a first address of the user associated with the messaging host system;~~

~~detecting the data message at the messaging host system;~~

~~forwarding a copy of the data message from the messaging host system to a wireless redirector host system via a wide area network connection between the messaging host system and the wireless redirector host system;~~

~~receiving a copy of a data message from the messaging host system at a wireless redirector host system via a wide area network connection, wherein the data message is from a sender and addressed to a first address of the user associated with the messaging host system;~~

processing the copy of the data message to repackage it with an outer envelope having a second address that is associated with the user's wireless mobile communication device;

~~upon~~—determining that the repackaged copy of the data message should be redirected from the wireless redirector host system to the wireless mobile communication device[[],];

transmitting the repackaged copy of the data message in real time from the wireless redirector host system to the wireless mobile communication device using the second address associated with the wireless mobile communication device via a wireless transmission network;

receiving a reply message that is repackaged in an outer envelope from the wireless mobile communication device, the outer envelope having an address associated with the wireless redirector host system; and

removing the outer envelope of the repackaged reply message at the wireless redirector host system and causing the reply message to be transmitted to the sender of the data message wherein the user's first address is configured as the reply message's originating address.

Claims 64-66. (Cancelled)

67. (Previously Presented) The method of claim 63, further comprising the steps of:

configuring a set of filtering rules for use by the wireless redirector host system in determining whether the data message should be redirected to the user's wireless mobile communication device; and

providing an access mechanism that allows the user to remotely configure and reconfigure the filtering rules by connecting to the wireless redirector host system from a remote terminal.

68. (Previously Presented) The method of claim 63, further comprising the steps of:

configuring a user profile database for use by the wireless redirector host system in determining whether the data message should be redirected to the user's wireless mobile communication device; and

providing an access mechanism that allows a system administrator of the messaging host system to remotely configure and reconfigure the user profile database by connecting to the wireless redirector host system from a remote terminal.

Claims 69-74. (Cancelled)

75. (Previously Presented) The method of claim 63, further comprising the step of:

transmitting a deactivation message associated with the user of the wireless mobile communication device to the wireless redirector host system; and

upon receiving the deactivation message, prohibiting the redirection of data messages for the user sending the deactivation message.

76. (Previously Presented) The method of claim 63, wherein the determining step includes the steps of:

accessing a user profile database including a list of authorized users; and

checking whether the user associated with the data message is an authorized user to determine whether the data message should be redirected to the user's wireless mobile communication device.

77. (Previously Presented) The method of claim 63,
wherein the determining step includes the steps of:

accessing a filter rules database including a list of
filters to be applied to data messages for a particular user; and
applying the filters to the data message to determine
whether the data message should be redirected to the user's
wireless mobile communication device.

Claim 78. (Cancelled)

79. (Previously Presented) The method of claim 63,
wherein the user's wireless mobile communication device is a
laptop computer.

80. (Previously Presented) The method of claim 63,
wherein the user's wireless mobile communication device is a two-
way paging computer.

81. (Previously Presented) The method of claim 80, wherein the two-way paging computer includes a wireless network interface for communicating with the wireless redirector host system via the wireless transmission network.

Claim 82. (Cancelled)

83. (Previously Presented) The method of claim 63, wherein the messaging host system is an Internet Service Provider (ISP) mail server.

Claims 84-85. (Cancelled)

86. (Previously Presented) The method of claim 63, wherein the wide area network connection coupling the messaging host system to the wireless redirector host system is an Internet connection.

87. (Previously Presented) The method of claim 67, wherein the access mechanism for remotely configuring and reconfiguring the filtering rules is a web-page interface.

88. (Previously Presented) The method of claim 68, wherein the access mechanism for remotely configuring and reconfiguring the user profile database is a web-page interface.

89. (Previously Presented) The method of claim 63, further comprising the steps of:

configuring a user profile database for use by the wireless redirector host system in determining whether the data message should be redirected to the wireless mobile communication device; and

storing, within the user profile database, the second address associated with the user's wireless mobile communication device.

90. (Previously Presented) The method of claim 89,
further comprising the steps of:

storing, within the user profile database, information
regarding the type and configuration of the wireless mobile
communication device.

Claim 91. (Cancelled)

92. (Previously Presented) The method of claim 63,
wherein the data message is a calendar event message.

Claims 93-119. (Cancelled)

120. (Currently Amended) A wireless redirector host system for continuously redirecting data messages between a messaging host system associated with a user and [[a]]the user's wireless mobile communication device, the system comprising:

means for receiving a copy of a data message via a wide area network connection, wherein the copy of the data message is forwarded from the messaging host system for a user, the data message originating from a sender and addressed to a first address of the user associated with the messaging host system;

means for processing [[a]] the copy of the data message to repackage it with an outer envelope having a second address that is associated with the user's wireless mobile communication device;

means for redirecting in real time the repackaged copy of the data message to the wireless mobile device upon arrival to the wireless redirector host system, responsive to determining that the repackaged copy of the data message should be redirected, the repackaged copy ~~of the data message to the wireless mobile communication device~~ using the second address associated with the wireless mobile communication device via a wireless transmission network;

means for receiving a reply message that is repackaged in an outer envelope from the wireless mobile communication device, the outer envelope having an address associated with the wireless redirector host system; and

means for removing the outer envelope of the repackaged reply message and for causing the reply message to be transmitted to the sender of the data message wherein the user's first address is configured as the reply message's originating address.

Claim 121. (Cancelled)